

Valeurs acoustiques

Opbouw (buitenruit - spouw - binnenruit)	Geluidswering in dB Rw (C;Ctr)	dB C	dB Ctr	max opp (645Pa) in m ²
4-15-4	30 (-1;-4)	29	26	1,90
4-15-4-15-4	33 (-2;-6)	31	27	3,17
4-15-4-15-33.2	36 (-2;-8)	34	28	3,17
5-15-4	32 (-1;-3)	31	29	2,80
6-15-6	32 (-1;-3)	31	29	5,00
6-15-33.2	34 (-1;-5)	33	29	3,00
6-15-4-15-4	36 (-2;-7)	34	29	3,92
6-15-4-15-33.2	37 (-2;-8)	35	29	3,92
4-15-33.2	35 (-1;-5)	34	30	1,90
8-15-8	35 (-2;-5)	33	30	9,50
6-15-4-15-6	36 (-2;-6)	34	30	5,86
6-15-5-15-6	36 (-2;-6)	34	30	6,60
5-15-6	34 (-1;-3)	33	31	3,80
6-15-4	36 (-1;-5)	35	31	3,00
33.2-15-33.2	36 (-1;-5)	35	31	1,90
8-15-6	36 (-2;-5)	34	31	6,50
4-15-44.2	37 (-2;-6)	35	31	2,80
4-15-44.4	37 (-2;-6)	35	31	2,80
5-15-44.2	37 (-2;-5)	35	32	3,20
6-15-4-15-44.2	39 (-2;-7)	37	32	5,34
33.2-15-4-15-33.2	39 (-2;-7)	37	32	3,17
44.2-15-4-15-33.2	39 (-2;-7)	37	32	3,92
44.4-15-4-15-33.2	39 (-2;-7)	37	32	3,92
44.4-15-4-15-6	39 (-2;-7)	37	32	5,34
5-15-8	37 (-1;-4)	36	33	5,50
10-15-10	37 (-1;-4)	36	33	15,10
12-15-10	38 (-2;-5)	36	33	17,30
12-15-12	38 (-2;-5)	36	33	19,26
8-15-44.2	38 (-2;-5)	36	33	5,50
8-15-44.4	38 (-2;-5)	36	33	5,50
44.4-15-5-15-6	39 (-1;-6)	38	33	6,05
6-15-5-15-44.2	39 (-1;-6)	38	33	6,05
44.2-15-4-15-44.2	41 (-2;-8)	39	33	5,15
44.2-15-5-15-44.2	41 (-2;-8)	39	33	5,95
44.2-15-6-15-44.2	41 (-2;-8)	39	33	6,66
44.2-15-8-15-44.2	41 (-2;-8)	39	33	7,56
44.4-15-4-15-44.2	41 (-2;-8)	39	33	5,15
44.4-15-5-15-44.2	41 (-2;-8)	39	33	5,95
44.4-15-6-15-44.2	41 (-2;-8)	39	33	6,66
44.4-15-8-15-44.2	41 (-2;-8)	39	33	7,56
6-15-44.2	37 (-1;-3)	36	34	3,80
6-15-44.4	37 (-1;-3)	36	34	3,80
10-15-8	38 (-2;-4)	36	34	11,40
44.2-15-33.2	39 (-1;-5)	38	34	2,80
44.2-15-44.2	39 (-1;-5)	38	34	3,20
44.4-15-33.2	39 (-1;-5)	38	34	2,80
44.2-15-44.4	39 (-1;-5)	38	34	3,20
8-15-6-15-6	39 (-2;-5)	37	34	7,67
8-15-6-15-8	39 (-2;-5)	37	34	10,40
8-15-8-15-8	39 (-2;-5)	37	34	11,56
4-15-44.2A	39 (-2;-5)	37	34	2,80
44.2A-15-4-15-33.2	41 (-2;-7)	39	34	3,92
44.2A-15-5-15-6	41 (-2;-7)	39	34	6,05

Valeurs acoustiques

Opbouw (buitenruit - spouw - binnenruit)	Geluidswering in dB Rw (C;Ctr)	dB C	dB Ctr	max opp (645Pa) in m²
12-15-8	38 (-2;-3)	36	35	13,15
6-15-55.2	39 (-1;-4)	38	35	5,00
8-15-6-15-44.2	40 (-2;-5)	38	35	7,18
8-15-8-15-44.2	40 (-2;-5)	38	35	8,50
44.4-15-6-15-8	40 (-2;-5)	38	35	7,18
44.4-15-8-15-8	40 (-2;-5)	38	35	8,50
6-15-44.2A	41 (-2;-6)	39	35	3,80
88.2-15-66.2	41 (-1;-5)	40	36	11,40
88.2-15-88.2	41 (-1;-5)	40	36	15,10
44.2A-15-33.2	41 (-1;-5)	40	36	2,80
8-15-44.2A	41 (-1;-5)	40	36	5,50
8-15-66.2A	41 (-1;-5)	40	36	9,50
55.2-15-44.2	41 (-2;-5)	39	36	3,80
66.2-15-66.2	42 (-1;-6)	41	36	9,50
44.2A-15-4-15-44.2	43 (-2;-7)	41	36	5,15
44.2A-15-6-15-44.2	43 (-2;-7)	41	36	6,66
44.2A-15-8-15-44.2	43 (-2;-7)	41	36	7,56
44.2A-15-5-15-44.2	43 (-2;-7)	41	36	5,95
6-15-66.2	40 (-1;-3)	39	37	5,90
8-15-66.2	41 (-1;-4)	40	37	9,50
8-15-55.2	41 (-2;-4)	39	37	6,50
44.2-15-44.2A	42 (-1;-5)	41	37	3,20
6-15-66.2A	42 (-1;-5)	41	37	5,90
66.2-15-44.2	42 (-2;-5)	40	37	5,50
66.2-15-44.4	42 (-2;-5)	40	37	5,50
44.2A-15-6-15-8	44 (-2;-7)	42	37	7,18
44.2A-15-8-15-8	44 (-2;-7)	42	37	8,50
55.2-15-66.2	42 (-1;-4)	41	38	6,50
8-15-6-15-66.2	43 (-2;-5)	41	38	10,40
8-15-66.2A	43 (-2;-5)	41	38	9,50
66.2-15-6-15-8	43 (-2;-5)	41	38	10,40
66.2-15-8-15-8	43 (-2;-5)	41	38	10,74
8-15-8-15-66.2	43 (-2;-5)	41	38	10,74
10-15-66.2	42 (-1;-3)	41	39	11,40
12-15-88.2	43 (-1;-4)	42	39	17,30
10-15-88.2	43 (-2;-4)	41	39	15,10
66.2-15-6-15-66.2	44 (-1;-5)	43	39	10,40
66.2-15-8-15-66.2	44 (-1;-5)	43	39	11,56
66.2A-15-6-15-66.2	46 (-2;-7)	44	39	10,40
88.2-15-8-15-66.2	45 (-1;-5)	44	40	15,00
88.2-15-8-15-88.2	45 (-1;-5)	44	40	19,26
66.2A-15-6-15-8	45 (-1;-5)	44	40	10,40
66.2A-15-8-15-66.2	46 (-2;-6)	44	40	11,56
66.2A-15-44.2	46 (-1;-5)	45	41	5,50
66.2-15-44.2A	46 (-1;-5)	45	41	5,50
44.2-15-66.2A	46 (-1;-5)	45	41	5,50
66.2-15-44.2A	46 (-1;-5)	45	41	5,50
10-15-66.2A	46 (-2;-5)	44	41	11,40
66.2A-15-8-15-88.2	47 (-2;-6)	45	41	15,00
66.2A-15-8-15-8	46 (-1;-4)	45	42	10,74
66.2A-15-88.2	47 (-1;-5)	46	42	11,40
66.2A-15-6-15-10	47 (-1;-4)	46	43	11,56